



A PLAYCORE Company

Water Playset Care



AquaWorx Water Playsets are comprised of both stainless steel and reinforced fiberglass and plastic components. These materials should be cleaned and cared for on a regular basis. Your unique Water Playset has been built with custom water features that require different levels of maintenance.

CLEANING YOUR WATER FEATURES SHOULD BE DONE ON A SEMI ANNUAL BASIS

Waterfeatures need to be cleaned on a regular basis. Calcium carbonate and hard water build-up need to be removed on a regular basis. Products such as CLR (Calcium, lime, and rust removal) and CalClean aid in the removal of calcium build up on aquatic surfaces. These products should be applied to the surface of the water features following the manufactures instructions. The fiberglass surfaces may need to be sanded with 600 then 800 grit sand paper if these products do not remove all of the scale and build up on the surface of the part. After the removal of the build up polishing with a buffer using a high cut compound will bring the surface back to its original luster. A high quality marine wax should be used to wax and seal.

CAUTION:WHEN USING ANY ELECTRIC TOOLS THE POOL OR FEATURE MUST BE DRAINED OF ALL WATER TO AVOID ELECTRICAL SHOCK AND A GFCI RECTICAL MUST BE USED.

Recommended Products available from West Marine:

Perfect-It™ Gelcoat Heavy Cutting Compound quickly removes heavy (up to P800) scratches, oxidation, water marks, and other defects from gelcoat. The "wet" formula extends the working time when using a polisher before new material is needed. Less material is used, and you get the job done faster.

Key Features

- Fast-cutting gelcoat formula for removing heavy oxidation and P800 scratches
- Formula provides longer wet time for extended product life and easier cleanup
- Suitable for all gelcoat surfaces including marine, RV and industrial
- Can be used with two- or three-step gelcoat finishing processes



Polish out sanding scratches with this pad.

Use this double-sided 100% wool compounding pad to refine 1200 grade and finer sanding scratches and other paint surface defects. Requires 3M 05752 (Model 15654536) Quick Connect Adapter, sold separately. The 3M Quick Connect system enables super quick pad changes and perfectly centers the pad. Pads are sold individually.

Key Features

- Double sided
- Good choice for refining 1200 grade and finer sanding scratches
- Quick connect system enables fast pad changes and perfectly centers pad



Polish fiberglass to a high gloss shine with less elbow grease.

Polish fiberglass and create lasting protection without the use of a paste wax. Preserves finish and look by shielding against outdoor corrosion; UV, stains, chalking, salt spray, and marine growth.

Key features

- Easy-to-use wax with a high gloss shine and long-lasting weather defense
- Enhances look while protecting finish
- No hard buffing required
- Provides protective coating of durability



CAUTION:WHEN USING ANY ELECTRIC TOOLS THE POOL OR FEATURE MUST BE DRAINED OF ALL WATER TO AVOID ELECTRICAL SHOCK AND A GFCI RECTICAL MUST BE USED.

Daily Water Playset Inspection Checklist



A PLAYCORE Company


Inspection Information

Facility Name

Inspection by

Date

-
- Inspect slide path to make sure there are no obstructions.
 - Look for chips, bubbles, or cracks in the gel coat.
 - Ensure no leaking joints.
 - Check for caulk that has peeled or worn away.
 - Tighten any loose fasteners and replace any that are missing.
 - Check for any excessive or abnormal movement of structural parts.
 - Check that the water flow amount to the slide is in range.
 - Visual Inspection of stairs and slide structure.
 - Make sure signage is placed correctly.

 **If any of these items are noticed, they must be corrected and repaired before the playset can be opened for use to ensure guest safety.**

For detailed information on water playset maintenance and cleaning please contact our service department at 888-426-8511.